

# FLEX-SEAL™ Skirting System

## Solves Spillage and Dust Control Problems

Flex-Seal™ Skirting System is a dynamic containment unit that fully seals the loading zone. It stops material spillage leaks, controls dust emissions and eliminates other resulting problems such as belt damage and mistracking. Conventional skirt clamps and systems may contain spillage of materials, but maintenance is typically difficult and time-consuming. And more importantly, the damage done to the conveyor belt is costly. The Flex-Seal Skirting System creates a parallel seal with the belt to be effective for your operation.




**Quick adjustment** by using the locking wedges on the clamp pins

**Anti-vibration pin** ensures pin remains locked




**Comes in easy-to-use** 1.2M lengths



**Rubber thickness** can vary from 8-19mm

**Angles the skirt rubber** so it seals with low contact pressure and without damaging the belt



**No hassle installation** with few parts and complete step-by-step instructions

## Features and Benefits

- **No belt damage.** With correct installation, the skirt rubber will not drag on the belt, causing premature wear or gouge marks in the belt cover. Such damage reduces belt cleaning efficiency and the life of the belt.
- **Safe service access.** All installation and maintenance work can be done safely from the sides of the conveyor. Climbing into the chute to work on nuts and bolts is not required.
- **Long service life.** Flex-Seal Skirting Systems are made of corrosion-protected components for tough duty. Replacement parts are available.

# FLEX-SEAL™ Skirting System

## Ordering Information

Flex-Seal Skirt System*		
Description	Ordering Number	Item Code
Flex-Seal Skirt System	CRMC2-FS-1	81995

\* Includes angle plate, one Bolt-On PAL PAK, and one 1.2M Clamp Bar.  
Skirt board and rubber not included.  
Skirt Rubber Thickness Ranges: 8mm to 19mm



Flex-Seal

Replacement Parts*		
Description	Ordering Number	Item Code
Angle Plate	CRMC2-SSAPK	81996
Bolt-On PAL PAK*	CRMC1-BPP	81984
Clamp Bar	CRMC1-CB	81990

\*Includes two bolt-on clamp pins and two clamp plates.



Bolt-On PAL PAK

Specifications	
Skirt Rubber Width and Thickness Range	
Width Required	150mm
Thickness Range	8-19mm


## Additional Information

Check out our other Skirting Systems,  
like the RMC1 or Flex-Lok.

RMC1



Flex-Lok



Flexco (Aust.) Pty. Ltd • 10 Solent Circuit • Baulkham Hills NSW 2153 • Australia  
Tel: 612-8818-2000 • Fax: 612-8824-6333 • E-mail: salesau@flexco.com

Visit [www.flexco.com](http://www.flexco.com) for other Flexco locations and products.

©2016 Flexible Steel Lacing Company. 12/20/16. For reorder: X1943

