


P-TYPE® Enhanced Service Advantage Cartridge HD Secondary Belt Cleaner

Reliable Cleaner with Improved Serviceability

The P-Type® ESAC combines the compact and highly efficient P-Type Secondary Cleaner with the Enhanced Service Advantage Cartridge. Not only simple to install using the versatile tensioner kit, the P-Type ESAC is also trouble-free to service, with the easy-to-use cartridge kit. The cartridge now gives you control over maintenance with three easy-to-use removal options. The P-Type ESAC is the reliable choice for a great cleaner at the right price.



P-TYPE® with Enhanced Service Advantage

Cartridge Heavy-Duty Secondary Belt Cleaner

Maximum Belt Speed

5 m/s (1000 FPM)

Temperature Rating

-35° C to 82° C (-30° F to 180° F)

Usable Blade Wear Length


9 mm (3/8")

Blade Material

Impact resistant, long-lasting tungsten carbide (C-Tip for mechanical fasteners, V-Tip for vulcanized belts)

Available for Belt Widths

600 to 3000 mm (24" to 120")



SINGLE CARTRIDGE

Overall Pole Length

Cleaner size + 1350 mm (54")

Maximum Conveyor Span

Cleaner size + 1050 mm (42")

Ordering Information

PC SAC HD Secondary Cleaner C-Tips and Bolt Tensioner

Belt Width		Ordering Number	Item Code
mm	in.		
600	24	PC600-SAC	78046
750	30	PC750-SAC	78047
900	36	PC900-SAC	78048
1050	42	PC1050-SAC	78049
1200	48	PC1200-SAC	78050
1350	54	PC1350-SAC	78051
1500	60	PC1500-SAC	78052
1800	72	PC1800-SAC	78053
1500	60	PC1500-2SAC	78054
1800	72	PC1800-2SAC	78055
2100	84	PC2100-2SAC	78056
2400	96	PC2400-2SAC	78057
3000	120	PC3000-2SAC	78058

Lead time: 1 working day

PV SAC HD Secondary Cleaner V-Tips and Bolt Tensioner

Belt Width		Ordering Number	Item Code
mm	in.		
600	24	PV600-SAC	78020
750	30	PV750-SAC	78021
900	36	PV900-SAC	78022
1050	42	PV1050-SAC	78023
1200	48	PV1200-SAC	78024
1350	54	PV1350-SAC	78025
1500	60	PV1500-SAC	78026
1800	72	PV1800-SAC	78027
1500	60	PV1500-2SAC	78028
1800	72	PV1800-2SAC	78029
2100	84	PV2100-2SAC	78030
2400	96	PV2400-2SAC	78031
3000	120	PV3000-2SAC	78032

Lead time: 1 working day

Lead time: 15 working days

NOTE: For easy blade changeout, remove cartridge with worn blades and replace with new blade cartridge kit. New blades can then be installed in the old cartridge for the next changeout.

Blade Cartridge Kits with C-Tips (Incl. blades, cartridge, and bolts)


Belt Width		Ordering Number	Item Code
mm	in.		
600	24	P-CARK-C24/600	78072
750	30	P-CARK-C30/750	78073
900	36	P-CARK-C36/900	78074
1050	42	P-CARK-C42/1050	78075
1200	48	P-CARK-C48/1200	78076
1350	54	P-CARK-C54/1350	78077
1500	60	P-CARK-C60/1500	78078
1800	72	P-CARK-C72/1800	78079
1500	60	P-CARK2-C60/1500	78088
1800	72	P-CARK2-C72/1800	78089
2100	84	P-CARK2-C84/2100	78090
2400	96	P-CARK2-C96/2400	78091
3000	120	P-CARK2-C120/3000	78092

Lead time: 1 working day

Blade Cartridge Kits with V-Tips (Incl. blades, cartridge, and bolts)

Belt Width		Ordering Number	Item Code
mm	in.		
600	24	P-CARK-V24/600	78080
750	30	P-CARK-V30/770	78081
900	36	P-CARK-V36/900	78082
1050	42	P-CARK-V42/1050	78083
1200	48	P-CARK-V48/1200	78084
1350	54	P-CARK-V54/1350	78085
1500	60	P-CARK-V60/1500	78086
1800	72	P-CARK-V72/1800	78087
1500	60	P-CARK2-V60/1500	78093
1800	72	P-CARK2-V72/1800	78094
2100	84	P-CARK2-V84/2100	78095
2400	96	P-CARK2-V96/2400	78096
3000	120	P-CARK2-V120/3000	78097

Lead time: 1 working day



Horizontal Clearance Required

114 mm (4-1/2")

Vertical Clearance Required

267 mm (10-1/2") (Single Cartridge)

311 mm (12-1/4") (Dual Cartridge)

Replacement Tips

Ordering Number	Item Code
ICT6	74535
PSA150	73156

Lead time: 1 working day

Tips Required per Cleaner Size

mm	in.	Tips Required
600	24	4
750	30	5
900	36	6
1050	42	7
1200	48	8
1350	54	9
1500	60	10
1800	72	12
2100	84	14
2400	96	16
3000	120	18

Authorized Distributor:



2 Woodlands Sector 1 • #01-21 • Woodlands Spectrum I • Singapore 738068

Tel: +65-6484-1533 • Fax: +65-6484-1531 • E-mail: asiasales@flexco.com

Visit www.flexco.com for other Flexco locations and products.

©2019 Flexible Steel Lacing Company. 02/18/19. For reorder: X2810