


DRX[™] 3000 Dynamic Beds

It's the Structure, Not the Bars

Flexco's DRXTM 3000 Dynamic Beds are designed with one simple goal: protect the belt. How we meet that goal is revolutionary. We've engineered superior belt protection into the entire structure - not just the bars. Sturdy components, robust construction and convenient maintenance make our line more durable and efficient. DRX 3000 takes this theory to the extreme with Impact Energy Absorbers that react to the most severe loads.



Impact Energy Absorbers compress up to 75mm (3") to disperse immense amounts of impact energy.

Features and Benefits

- **Protect the belt.** The Velocity Reduction Technology[™], including Impact Bar Supports and the Impact Energy Absorbers, ensure a level of protection unlike any other. Less belt wear and damage, less rebounding and material degradation and two levels of impact absorbing force reduction.
- **Application specific options.** Perfect for the most rugged, heavy-duty drop zones at any facility, the DRX 3000 can meet your specific needs.



DRX™ 3000 Dynamic Beds

Specifications and Guidelines

- Maximum Belt Speed 5M/sec (1000 fpm)
- Max Temperature Rating -40°C to 82°C (-40°F to 180°F)
- Impact Bar Material UHMW Polyethylene, rubber cushion and aluminum extrusion
- Available for Belt Widths 1050 to 2400mm (42" to 96")
- Impact Energy
 Max Lump Weight (kg) x Drop Height (m)
 200 to 400 kg-m (1500 to 3000 lb-ft)
- Tonnage Rating See table below

Ordering Information


| DRX3000 | | | | | | |
|------------|-----|-----------------|-----------------------|-------|-----------------------|-------|
| | | | 1.5m Beds, 20° Trough | | 1.5m Beds, 35° Trough | |
| Belt Width | | Tonnage Rating | Ordering | Item | Ordering | Item |
| mm | in. | metric tons/hr) | Number | Code | Number | Code |
| 1050 | 42 | 26100 | DRXD-42-520 | 76912 | DRXD-42-535 | 76919 |
| 1200 | 48 | 29000 | DRXD-48-520 | 76913 | DRXD-48-535 | 76920 |
| 1350 | 54 | 34800 | DRXD-54-520 | 76914 | DRXD-54-535 | 76921 |
| 1500 | 60 | 37700 | DRXD-60-520 | 76915 | DRXD-60-535 | 76922 |
| 1800 | 72 | 40600 | DRXD-72-520 | 76916 | DRXD-72-535 | 76923 |
| 2100 | 84 | 46400 | DRXD-84-520 | 76917 | DRXD-84-535 | 76924 |
| 2400 | 96 | 57900 | DRXD-96-520 | 76918 | DRXD-96-535 | 76925 |

Lead time: 20 working days

Additional Information

The Impact Bed Handy Wrench will come in useful during maintenance and installation.

A ratcheting wrench with 2 common socket sizes (19mm & 24mm) for installation and maintenance of impact beds.



Authorized Distributor:

FLEXCO

No: 1. Flexco Lane • Maduravoyil – Porur Service Road • Vanagaram Village • Chennai – 95 • India Tel: +91-44-6551-7771 • E-mail: info.india@flexco.com