

### Engineered for Precision Belt Splicing

Splices in monolithic belting must ensure tight pitch tolerance and be free from pinhole air pockets. Everything about the Amigo™ has been designed to do just that. And in typical Novitool® design, it was made to do it with ease, safety, and speed.


Custom templates secure the belt when cut to ensure accurate pitch control. Then the contactless heating process splices the belt in less than one minute and finishes with a controlled amount of clash. To ensure quality splices, pinholes are avoided through engineered solutions such as the pre-heat function to remove moisture from the belt ends; the shielded heat zone for consistent heating in various environmental conditions; and the contactless heating method. Accuracy, speed, and operator safety are fully integrated into the Amigo design making it an ideal splicing tool for in-shop or on-site splicing.



**Integrated Belt Cutter** maintains accurate pitch in a single pass



**Contactless Heating** provides for a controlled amount of clash without actual contact with the heat source



**Shielded Heat Zone and Temperature Control** ensures splice parameter consistency regardless of ambient temperatures



Operates on **Single Phase 115V or 230V**




**Interchangeable Splice Templates** for precise pitch splicing of belts from various belt manufacturers



**Digital Time Control** with quick, simple splice settings; the **Pre-Heat Setting** can be used to remove moisture and avoid pinholes



**Custom Transport Case** for easy storage and transportation




#### Amigo™ Dimension Information


	DIMENSIONS	WEIGHT
Machine	1425 mm (56.1") × 315 mm (12.4") × 170 mm (6.7")	38.5 kg (85 lb)
Transport Case (includes additional templates and support equipment)	1700 mm (66.9") × 490 mm (19.3") × 385 mm (15.2")	36.3 kg (80 lb)
<b>Total Weight</b>		<b>74.8 kg (165 lb)</b>

\*Patent Number: US 8,770,253 B2, other patents pending

## Safety Features of the Amigo™




**Integrated Cutter:** Operator is protected from blade during single pass cutting operation.



**Cutter Storage Position:** Cutter must be in storage position for splicing function to operate.



**Shielded Heat Zone:** Guard must be closed for heat emitter to function. Operator is protected from heat source during splicing.



**Cool Zone:** Heater stows and cools inside unit as belt ends are butt-welded together.

## NOVITOOL® AMIGO™ Splice Press for Monolithic Belts

Amigo™ Press and Cable Ordering Information			
	Ordering Number	Item Code	
<b>Press</b>			
1065 mm (42")	AMIGO-1000-SPLICEPRESS	08545	
<b>Cables</b>			
230 volt; single phase; 10 amp	AMIGO-1000-CABLE-1X230-AS3112	08727	

NOTE: Press, cable, and templates are all purchased separately.

Amigo™ Belt Template Ordering Information				
Item Code	Ordering Number	Belt Manufacturer	Belt Style	Belt Type
<b>Templates</b>				
08592	AMIGO-1000-TMPLT-08592	Volta	SuperDrive™	FMW & FMB FHW & FHB
08593	AMIGO-1000-TMPLT-08593	Intralox®	ThermoDrive®	8050
		Mafdel	DEL/DRIVE	8026 DD25
08594	AMIGO-1000-TMPLT-08594	Habasit	Cleandrive™	CD.M50.S-UA.CB
				CD.M50.S-UA.WB
				CD.M25.S-UA.CB
				CD.M25.S-UA.WB
08595	AMIGO-1000-TMPLT-08595			Flat
08596	AMIGO-1000-TMPLT-08596	Gates® Mectrol®	PosiClean®	PC10
		UBR	1" PurClean	PC20
08597	AMIGO-1000-TMPLT-08597	Gates® Mectrol®	CenterClean®	CC40
		Daisler®	RE0clean®	AT40
		UBR	Center Drive PurClean	CD3BLSS
08603	AMIGO-1000-TMPLT-08603	Ammeraal	Aeon	Aeon-50
08710	AMIGO-1000-TMPLT-08710	Cog-veyor Systems Inc.	Cog-veyor	UBM
				UWM
				PBH
				PWH
08739	AMIGO-1000-TMPLT-08739	Beltservice Corporation	Magnethane™	PD1
08741	AMIGO-1000-TMPLT-08741			Flat w/Spikes
08776	AMIGO-1000-TMPLT-08776	Gates® Mectrol®	PosiLace™	PC20
		UBR	Hinge Lace	CC40 FC12
08788	AMIGO-1000-TMPLT-08788	Volta	DualDrive™	AT25
				RE0clean®
				2" PurClean
				Mini DualDrive™
				Mini SuperDrive™
08847	AMIGO-1000-TMPLT-08847	Volta	Hinge Splice	FMW & FMB FHW & FHB
08849	AMIGO-1000-TMPLT-08849	Ammeraal Beltech	Soliflex PRO/ Soliflex PRO mini	FMB FHB FMB FHB
08855	AMIGO-1000-TMPLT-08855	Mafdel	POSITIVEBELT	M (2.5-5mmH)
08856	AMIGO-1000-TMPLT-08856	Mafdel	DEL/DRIVE	Soliflex TPU Soliflex TPE

Amigo™ Optional Accessories		
	Ordering Number	Item Code
Skiving Tool	RTBS Rough Top Skiver	03239
Replacement Blades for Amigo	AMIGO-1000-BLADES-5	08587
High – Low Temp Friction Tape for Flat Belts	AMIGO-FRICTIONTAPE-33X25	08604

Authorised Distributor:

Flexco (Aust.) Pty. Ltd • 10 Solent Circuit • Baulkham Hills NSW 2153 • Australia  
Tel: 612-8818-2000 • Fax: 612-8824-6333 • E-mail: salesau@flexco.com

Visit [www.flexco.com](http://www.flexco.com) for other Flexco locations and products.

©2019 Flexible Steel Lacing Company. Novitool® is a registered trademark. 07/31/19. For reorder: X3518  
Intralox® and ThermoDrive® are registered trademarks of Lairam L.L.C.

