



TUG™ HD® Belt Clamps

Ultimate Grip and Superior Strength Combine to Secure the Belt

Flexco understands that worker safety is a top priority when repairing belts carrying larger loads. Flexco TUG™ HD® Belt Clamps are designed to secure the belt for belt repair meeting the most stringent safety test standards. Available in 6 and 8 ton versions, TUG HD Belt Clamps provide even tensioning across the entire belt width for ultimate strength. Modular components allow for increased versatility and portability.



Clamps over the belt for greater strength



Acme thread offers superior grip strength and allow operators the chance to slowly release the belt after maintenance



Extruded non-slip grip pattern on aluminum bars provides ultimate holding power



Easy to carry heat-treated aluminum clamp bars



Clamp Ends feature increased capacity for easier clamp bar insertion

Features and Benefits:

- **Safety first.** Third-party tested. Safety factors of clamp ratings meet or exceed industry standards.
- **Easy belt maintenance.** A single pair can be used to block off belt for maintenance.
- **Belt versatility.** Can be used on multiple conveyor belting types including flat, sidewall, chevron, and other specialty profiles.
- **Engineered for tough conditions.** Designed with high-grade aluminum bars and structural steel clamp ends. Shock absorbing end caps are designed to protect the bars from hammer use and drops.
- **Ideal for larger loads.** 6 and 8 ton load capacity ratings and belt widths up to 96" (2400 mm).

Available versions


6 Ton

8 Ton


Easy on-site identification clamp labels are color-coded blue for 6 Ton and black for 8 Ton.

Secure Versatility

TUG™ HD® Belt Clamps are engineered for heavy-duty applications and can be used with a variety of materials and belt types.



6 ton clamps are available for belts up to 72" (1800 mm) wide and up to 2" (50 mm) thick, while the 8 ton clamps are available for belts up to 96" (2400 mm) wide and up to 2 1/4" (55 mm) thick.



Can be used on solid woven PVC/PVG or rubber cover plied belting.



TUG HD Belt Clamps are perfect for use with sidewall belts. Ordering numbers for a pair of 12" (300 mm) bars are TUG6B-12-AL, TUG8B-12-AL.

TUG™ HD® Belt Clamps

TUG™ HD® Belt Clamps Specifications

Version	Maximum Belt Thickness	Clamp Screw Torque	Force per Clamp	Clamp Force on Belt
TUG6	2" (50 mm)	120 ft. lbs. (162 Nm)	3 Metric Tons (6,600 lbs)	6 Metric Tons (13,200 lbs)
TUG8	2.25" (55 mm)	120 ft. lbs. (162 Nm)	4 Metric Tons (8,800 lbs)	8 Metric Tons (17,600 lbs)

Note: 1.25" (32 mm) maximum belt thickness when using TUG6E clamp ends with Far-Pul® HD® bars.

TUG™ HD® Belt Clamps COMPLETE Ordering Information

Belt Width		Ordering Number		TUG6 Weight		TUG8 Weight	
in.	mm	6 Ton	8 Ton	lbs.	kgs.	lbs.	kgs.
Up to 36	Up to 900	TUG6-36-AL	TUG8-36-AL	134	61	178	81
Up to 42	Up to 1050	TUG6-42-AL	TUG8-42-AL	141	64	189	86
Up to 48	Up to 1200	TUG6-48-AL	TUG8-48-AL	148	67	200	91
Up to 54	Up to 1400	TUG6-54-AL	TUG8-54-AL	155	70	211	96
Up to 60	Up to 1600	TUG6-60-AL	TUG8-60-AL	162	73	222	101
Up to 72	Up to 1800	TUG6-72-AL	TUG8-72-AL	176	80	244	111
Up to 84	Up to 2200	N/A	TUG8-84-AL	N/A		266	121
Up to 96	Up to 2400	N/A	TUG8-96-AL	N/A		288	131

Note: A complete set of TUG™ HD® Belt Clamps includes four aluminum clamp bars and four steel clamp ends. Contact customer service for information on steel bars.

TUG™ HD® Belt Clamps PAIR Ordering Information

Belt Width		Ordering Number		TUG6 Weight		TUG8 Weight	
in.	mm	6 Ton	8 Ton	lbs.	kgs.	lbs.	kgs.
Up to 36	Up to 900	TUG6P-36-AL	TUG8P-36-AL	67	30	89	40
Up to 42	Up to 1050	TUG6P-42-AL	TUG8P-42-AL	71	32	95	43
Up to 48	Up to 1200	TUG6P-48-AL	TUG8P-48-AL	74	34	100	45
Up to 54	Up to 1400	TUG6P-54-AL	TUG8P-54-AL	78	35	106	48
Up to 60	Up to 1600	TUG6P-60-AL	TUG8P-60-AL	81	37	111	50
Up to 72	Up to 1800	TUG6P-72-AL	TUG8P-72-AL	88	40	122	55
Up to 84	Up to 2200	N/A	TUG8P-84-AL	N/A		133	60
Up to 96	Up to 2400	N/A	TUG8P-96-AL	N/A		144	65

Note: A pair of TUG™ HD® Belt Clamps includes two aluminum clamp bars and two steel clamp ends. Contact customer service for information on steel bars.

TUG™ HD® Belt Clamps REPLACEMENT BARS PAIR Ordering Information

Belt Width		Ordering Number		TUG6 Weight		TUG8 Weight	
in.	mm	6 Ton	8 Ton	lbs.	kgs.	lbs.	kgs.
12	300	TUG6B-12-AL	TUG8B-12-AL	7	3	11	5
Up to 36	Up to 900	TUG6B-36-AL	TUG8B-36-AL	21	10	33	15
Up to 42	Up to 1050	TUG6B-42-AL	TUG8B-42-AL	25	11	39	17
Up to 48	Up to 1200	TUG6B-48-AL	TUG8B-48-AL	28	13	44	20
Up to 54	Up to 1400	TUG6B-54-AL	TUG8B-54-AL	32	14	50	22
Up to 60	Up to 1600	TUG6B-60-AL	TUG8B-60-AL	35	16	55	25
Up to 72	Up to 1800	TUG6B-72-AL	TUG8B-72-AL	42	19	66	30
Up to 84	Up to 2200	N/A	TUG8B-84-AL	N/A		77	35
Up to 96	Up to 2400	N/A	TUG8B-96-AL	N/A		88	40

Note: A replacement complete set of TUG™ HD® Belt Clamps includes two aluminum clamp bars. Contact customer service for information on steel bars.

TUG™ REPLACEMENT CLAMP END

Ordering Number	Weight	
	lbs.	kgs.
TUG6E	23	10
TUG8E	28	13

Note: Includes one Steel Clamp End

Aluminum Content

Aluminum Alloy Type	Percent	
	Mg Magnesium	Ti Titanium
6061	1.00%	0%

Authorized Distributor:



2525 Wisconsin Avenue • Downers Grove, IL 60515-4200 • USA
Tel: (630) 971-0150 • Fax: (630) 971-1180 • E-mail: info@flexco.com

Visit www.flexco.com for other Flexco locations and products.

©2016 Flexible Steel Lacing Company. 05-07-19. For Reorder: X4434

