

Flex-Seal™ Skirting System

Seals and Prevents Spillage of All Raw Materials and Clinker

Use Flex-Seal™ Skirting in areas throughout the cement process where the load zone needs to be fully sealed. It is especially effective in the transfers between the primary crusher and the stockpile, as well as in the secondary crusher, where confined spaces make cleanup challenging, if not impossible. Flex-Seal is also ideal on belts carrying clinker to storage or finish mills where dust needs to be contained. The Flex-Seal Skirting System creates a parallel seal with the belt to be effective for your cement operation.




Quick adjustment by using the locking wedges on the clamp pins

Anti-vibration pin ensures pin remains locked




Comes in easy-to-use 1.2M (4') lengths




Rubber thickness can vary from 8-19mm (5/16" to 3/4")

Angles the skirt rubber so it seals with low contact pressure and without damaging the belt



No hassle installation with few parts and complete step-by-step instructions



Standard **Urethane Skirting** is available for high-abrasion applications in areas such as clinker storage and near the finish mills.

Features and Benefits

- **No belt damage.** With correct installation, the skirt rubber will not drag on the belt, causing premature wear or gouge marks in the belt cover. Such damage reduces belt cleaning efficiency and the life of the belt.
- **Safe service access.** All installation and maintenance work can be done safely from the sides of the conveyor. Climbing into the chute to work on nuts and bolts is not required.
- **Long service life.** Flex-Seal™ Skirting Systems are made of corrosion-protected components for tough duty. Replacement parts are available.

FLEX-SEAL™ Skirting System

Ordering Information

Flex-Seal™ Skirt System*		
Description	Ordering Number	Item Code
Flex-Seal™ Skirt System	RMC2-FS	76558

* Includes angle plate, one Bolt-On PAL PAK, and one 1.2M (4') Clamp Bar.
Skirt board and rubber not included.
Skirt Rubber Thickness Ranges: 8mm to 19mm (5/16" to 3/4")



Flex-Seal™

Replacement Parts*		
Description	Ordering Number	Item Code
Angle Plate	RMC2-AP	76559
Bolt-On PAL PAK*	RMC1-BPP	76415
Clamp Bar	RMC1-CB	75820

*Includes two bolt-on clamp pins and two clamp plates.



Bolt-On PAL PAK

Specifications	
Skirt Rubber Width and Thickness Range	
Width Required	150mm (6")
Thickness Range	8-19mm (5/16"-3/4")

Standard Urethane Skirting

For high-abrasion applications in areas such as clinker storage and near the finish mills, urethane skirting offers a more wear-resistant material than typical rubber, often providing as much as 3-4 times the wear life in similar applications. The lower coefficient of friction reduces strain on the system. Suitable for most applications around the cement plant: single direction or reversing belts, wet or dry conditions, old or new belts, vulcanized or mechanically-spliced systems, soft durometer (65A) urethane offers exceptional tear resistance to ensure a good seal and long belt life.

- 7.6M' (25) roll size ensures easy transportation, while the 35° chamfer eliminates the typical skirting break-in period.
- Rated for temperatures from -30°C to 82°C (-20°F to 180°F).



Standard Urethane Skirting*									
Height		Thickness		Length		Chamfer	Ordering Number	Item Code	Wt. Lbs.
mm	in.	mm	in.	ft	m				
150	6	12	1/2	25	7.6	35°	SKPU-6x1/2x25	90283	40.0
150	6	20	3/4				SKPU-6x3/4x25	90284	60.0
200	8	12	1/2				SKPU-6x1/2x25	90285	58.0
200	8	20	3/4				SKPU-6x3/4x25	90286	86.0

*Lead time: 1 working day

Authorized Distributor: