FGP Food Grade Precleaner

USDA Certified Precleaner Meets Highest Standards for Industrial Baking Applications

The FGP Food Grade Precleaner from Flexco is the most effective food grade cleaner on the market at removing dough, flour, oils, frosting, and other sticky materials from the conveyor belt. And it is easy to install, maintain, and disassembles in a snap for regular cleaning, allergen cleansing, and sanitization. That means your pre-bake or post-bake lines can be up and running again fast. The FGP Precleaner works on any belt from 100mm to 1500mm and the blade is available in white, blue, metal detectable blue, and dual durometer metal detectable blue FDA-approved food grade materials.



Cleaner blades are available in blue, white, dual durometer metal detectable blue, and metal detectable blue



- The FGP Precleaner is:
- Made from FDA approved materials
- USDA certified
- Compliant with EU 1935/2004 Food Contact Regulation
- Accepted by Health Canada


Cleaning blade designed to achieve optimal cleaning efficiency in even the most demanding industrial baking applications

> Simple to adjust spring tensioning unit ensures for maximum cleaning benefits

Features and Benefits:

- Minimal hardware so installation, tensioning, and blade replacement are easy.
- Simple design with stainless steel components and food grade materials limit crevices and opportunities for bacteria growth.
- Easily tensioned to minimize blade wear, eliminate belt damage, and maximize cleanability.
- Optional metal detectable blue blade for additional protection against food contamination.
- Dual durometer blade for uneven or soft cover belts.
- Available in standard blade widths for belts from 300 mm to 1500 mm. Blades can be cut down to appropriate length.
- Compatible with endless and mechanical splices. Suitable for use on modular belting.

Simple snap-in-place blade design allows for easy disassembly in less than a minute – no mechanical fasteners used in the product flow and no need to remove cleaner from structure for cleaning or replacement. Reassembly is just as quick so your line is up and running again fast





Patents: D776,396 and 0029948222-0001

www.flexco.com


FGP Food Grade Precleaner

Specifications:

• Temperature Range UHMW: -29°C to 60°C Dual Durometer: (0°C to 60°C

• Blade Height 76 mm

- Blade Width Range 102 to 1524 mm
- Pole/Mounting Material 304 Stainless Steel
- Blade Hardness UHMW: 63D Shore Hardness Urethane: 33D Shore Hardness
- Pulley Diameter Range 50 to 267 mm
- Blade Material Food-grade UHMW, UHMW with Stainless Steel, or Urethane with PVC



How to choose the correct size blade for your conveyor.

- 1. Measure your belt width.
- 2. Choose the Blade Width that corresponds to your belt width.
- 3. Measure your conveyor width.
- 4. Verify the Maximum Conveyor Width shown in the selection chart is larger than your conveyor width. If your conveyor width is smaller than the maximum width shown, choose the next larger blade width that accommodates your conveyor width.
- 5. Blade and/or pole can be cut to users required length. Pole must be 50mm longer than the outside width of conveyor structure at the mounting location.


Pole Lengths							
Pole Length	Standard Blade Length	Minimum Blade Length	Minimum Conveyor Width at Cleaner Mounting Location	Maximum Conveyor Width at Cleaner Mounting Location			
mm	mm	mm	mm	mm			
610	305	229	279	556			
813	457	229	356	708			
965	610	229	508	861			
1067	813	457	660	1013			
1219	965	457	813	1165			
1372	1067	457	965	1318			
1524	1219	457	1118	1470			
1676	1372	457	1270	1623			
1829	1524	457	1422	1775			


*Pole length = blade length + 300mm on standard cleaners.


FGP Food Grade Precleaner										
Blade Width	Maximum Conveyor Width	Weight	White Blade		Blue Blade		Blue Metal DetectableBlade		Blue Dual Durometer Blade*	
mm	mm	kg.	Ordering Number	ltem Code	Ordering Number	ltem Code	Ordering Number	ltem Code	Ordering Number	ltem Code
305	559	3.0	FGP-W3-12	56009	FGP-BL3-12	56000	FGP-MD3-12	56027	FGP-MDDD3-12	56018
457	711	3.5	FGP-W3-18	56010	FGP-BL3-18	56001	FGP-MD3-18	56028	FGP-MDDD3-18	56019
610	864	3.9	FGP-W3-24	56011	FGP-BL3-24	56002	FGP-MD3-24	56029	FGP-MDDD3-24	56020
762	1016	4.3	FGP-W3-30	56012	FGP-BL3-30	56003	FGP-MD3-30	56030	FGP-MDDD3-30	56021
914	1168	4.8	FGP-W3-36	56013	FGP-BL3-36	56004	FGP-MD3-36	56031	FGP-MDDD3-36	56022
1067	1321	5.2	FGP-W3-42	56014	FGP-BL3-42	56005	FGP-MD3-42	56032	FGP-MDDD3-42	56023
1219	1473	5.6	FGP-W3-48	56015	FGP-BL3-48	56006	FGP-MD3-48	56033	FGP-MDDD3-48	56024
1372	1626	6.0	FGP-W3-54	56016	FGP-BL3-54	56007	FGP-MD3-54	56034	FGP-MDDD3-54	56025
1524	1778	6.4	FGP-W3-60	56017	FGP-BL3-60	56008	FGP-MD3-60	56035	FGP-MDDD3-60	56026


*Dual durometer blade is not compliant with Health Canada or EU 1935/2004.

F	FGP Optional Mounting Brackets (Bolt or Weld)						
Description		Ordering Number	ltem Code				
1	Frame Mount	FGP-MOUNT-FRAME	56585				
2	Flange Bearing Mount	FGP-MOUNT-FLANGE-BEARING	56586				
3	Base Bearing Mount	FGP-MOUNT-BASE-BEARING	56587				
4	Two-Piece Mount	FGP-MOUNT-TWO-PIECE	56588				









.....

Authorised Distributor:

.....



Flexco Europe GmbH • Maybachstrasse 9 • 72348 Rosenfeld • Germany Tel: +49-7428-9406-0 • Fax: +49-7428-9406-260 • E-mail: europe@flexco.com

Visit www.flexco.com for other Flexco locations and products.