

Novitool® Amigo™ Splice Press for Monolithic Belts



Create an Endless Splice That's Easy on Your Dough

For industrial bakers, it's all about the dough. The Amigo™ Splice Press creates a smooth, endless splice that is less likely to stick to the dough, tear the dough, or mark the dough. And, in post-bake applications where baked products are still contacting the belt directly, the quality of the endless splice is critical. Splices in monolithic belting must ensure tight pitch tolerance and be free from pinhole air pockets. Everything about the Amigo has been designed to do just that. And in typical Novitool® design, it was made to do it with ease, safety, and speed.

Custom templates secure the belt when cut to ensure accurate pitch control. Then the contactless heating process splices the belt in less than one minute and finishes with a controlled amount of clash. To ensure quality splices, pinholes are avoided through engineered solutions such as the pre-heat function to remove moisture from the belt ends; the shielded heat zone for consistent heating in various environmental conditions; and the contactless heating method. Accuracy, speed, and operator safety are fully integrated into the Amigo design, making it an ideal splicing tool for in-shop or on-site splicing.



Integrated Belt Cutter
maintains accurate pitch in a single pass



Contactless Heating
provides for a controlled amount of clash without actual contact with the heat source



Shielded Heat Zone and Temperature Control
ensures splice parameter consistency regardless of ambient temperatures



Operates on **Single Phase**
115V or 230V



Interchangeable Splice Templates for precise pitch splicing of belts from various belt manufacturers



Digital Time Control
with quick, simple splice settings; the **Pre-Heat Setting**

can be used to remove moisture and avoid pinholes



Custom Transport Case
for easy storage and transportation



Intertek
4003271
Cert. to CAN/CSA
Std. C22.2 No. 88



Intertek
4003271
Conforms to
IEC STD 60204-1
& EN STD 60204-1

*Patent Number: US 8,770,253 B2, other patents pending

Amigo™ Dimension Information

	DIMENSIONS	WEIGHT
Machine	1425 mm × 315 mm × 170 mm	38.5 kg
Transport Case (includes additional templates and support equipment)	1700 mm × 490 mm × 385 mm	36.3 kg
Total Weight		74.8 kg

Safety Features of the Amigo™



Integrated Cutter: Operator is protected from blade during single pass cutting operation.



Cutter Storage Position: Cutter must be in storage position for splicing function to operate.



Shielded Heat Zone: Guard must be closed for heat emitter to function. Operator is protected from heat source during splicing.



Cool Zone: Heater stows and cools inside unit as belt ends are butt-welded together.

NOVITOOL® AMIGO™ Splice Press for Monolithic Belts

Amigo™ Press and Cable Ordering Information

	Ordering Number	Item Code
Press		
1065 mm (42")	AMIGO-1000-SPLICEPRESS	08545
Cables		
115 volt; single phase; 15 amp	AMIGO-1000-CABLE-1X115	Choose 115V or 230V. You will be contacted for appropriate plug configuration.
230 volt; single phase; 7.5 amp	AMIGO-1000-CABLE-1X230	

NOTE: Press, cable, and templates are all purchased separately.

Amigo™ Belt Template Ordering Information

Item Code	Ordering Number	Belt Manufacturer	Belt Style	Belt Type
Templates				
08592	AMIGO-1000-TMPLT-08592	Volta	SuperDrive™	FMW & FMB FHW & FHB
08593	AMIGO-1000-TMPLT-08593	Intralox®	ThermoDrive®	8050
		Mafdel	DEL/DRIVE	8026 DD25
08594	AMIGO-1000-TMPLT-08594	Habasit	Cleandrive™	CD.M50.S-UA.CB CD.M50.S-UA.WB CD.M25.S-UA.CB CD.M25.S-UA.WB
08595	AMIGO-1000-TMPLT-08595			Flat
08596	AMIGO-1000-TMPLT-08596	Gates® Mectrol®	PosiClean®	PC10 PC20
		UBR	1" Purclean	PS2
08597	AMIGO-1000-TMPLT-08597	Gates® Mectrol®	CenterClean®	CC40
		UBR	Center Drive PurClean	CD3BLSS
08603	AMIGO-1000-TMPLT-08603	Ammeraal	Aeon	Aeon-50
08710	AMIGO-1000-TMPLT-08710	Cog-veyor Systems Inc.	Cog-veyor	UBM UWM PBH PWH
				PD1
				Flat w/Spikes
				PC20 CC40
08739	AMIGO-1000-TMPLT-08739	Beltservice Corporation	Magnethane™	FC12
				N/A
08741	AMIGO-1000-TMPLT-08741	Gates® Mectrol®	PosiLace™	REO-T50 DB REO-T50 SB REO-T50 W REO-M25 DB
			Hinge Lace	PB3
08776	AMIGO-1000-TMPLT-08776	Daisler®	REOclean®	FMW & FMB FHW & FHB
				FMB FHB
		Volta	Mini DualDrive™	FMB FHB
			Mini SuperDrive™	FMB FHB
08796	AMIGO-1000-TMPLT-08796	Ammeraal Beltech	Soliflex Pro	N/A
08847	AMIGO-1000-TMPLT-08847	Volta	Hinge Splice	M (2.5-5mmH)
08855	AMIGO-1000-TMPLT-08855	Mafdel	POSITIVEBELT	P02-L
08856	AMIGO-1000-TMPLT-08856	Mafdel	DEL/DRIVE	DD50

Amigo™ Optional Accessories

	Ordering Number	Item Code
Skiving Tool	RTBS Rough Top Skiver	03239
Replacement Blades for Amigo	AMIGO-1000-BLADES-5	08587
High – Low Temp Friction Tape for Flat Belts	AMIGO-FRICTIONTAPE-33X25	08604

Authorised Distributor: