Novitool[®] Amigo[™] Splice Press for Monolithic Belts

bNovitool°

Create an Endless Splice That's Easy on Your Dough

For industrial bakers, it's all about the dough. The Amigo[™] Splice Press creates a smooth, endless splice that is less likely to stick to the dough, tear the dough, or mark the dough. And, in post-bake applications where baked products are still contacting the belt directly, the quality of the endless splice is critical. Splices in monolithic belting must ensure tight pitch tolerance and be free from pinhole air pockets. Everything about the Amigo has been designed to do just that. And in typical Novitool[®] design, it was made to do it with ease, safety, and speed.

Custom templates secure the belt when cut to ensure accurate pitch control. Then the contactless heating process splices the belt in less than one minute and finishes with a controlled amount of clash. To ensure quality splices, pinholes are avoided through engineered solutions such as the pre-heat function to remove moisture from the belt ends; the shielded heat zone for consistent heating in various environmental conditions; and the contactless heating method. Accuracy, speed, and operator safety are fully integrated into the Amigo design, making it an ideal splicing tool for in-shop or on-site splicing.



Integrated Belt Cutter maintains accurate pitch in a single pass



Contactless Heating provides for a controlled amount of clash without actual contact with the heat source



Shielded Heat Zone and Temperature Control ensures splice parameter consistency regardless of ambient temperatures



Operates on Single Phase 115V or 230V



Interchangeable Splice Templates for precise pitch splicing of belts from various belt manufacturers



Digital Time Control with quick, simple splice settings; the **Pre-Heat Setting**

can be used to remove moisture and avoid pinholes

Custom **Transport Case** for easy storage and transportation






Amigo™ Dimension Information				
	DIMENSIONS	WEIGHT		
Machine	1425 mm × 315 mm × 170 mm	38.5 kg		
Transport Case (includes additional templates and support equipment)	1700 mm × 490 mm × 385 mm	36.3 kg		
Total Weight		74.8 kg		

*Patent Number: US 8,770,253 B2, other patents pending

www.flexco.com



Safety Features of the Amigo™



Integrated Cutter: Operator is protected from blade during single pass cutting operation.



Cutter Storage Position: Cutter must be in storage position for splicing function to operate.



Shielded Heat Zone: Guard must be closed for heat emitter to function. Operator is protected from heat source during splicing.



Cool Zone: Heater stows and cools inside unit as belt ends are butt-welded together.

NOVITOOL[®] AMIGO[™] Splice Press for Monolithic Belts

Amigo [™] Press and Cable Ordering Information					
	Ordering Number	ltem Code			
Press					
1065 mm (42")	AMIG0-1000-SPLICEPRESS	08545			
Cables					
230 volt; single phase; 10 amp	AMIG0-1000-CABLE-1X230-AS3112	08727	(\cdot)		

NOTE: Press, cable, and templates are all purchased separately.

ltem Code	Ordering Number	Belt Manufacturer	Belt Style	Belt Type
Templa	tes			
08592		Volta	SuperDrive™	FMW & FMB
08592	AMIG0-1000-TMPLT-08592			FHW & FHB
08593	AMIGO-1000-TMPLT-08593	Intralox [®] ThermoDrive [®]	ThermoDrive®	8050
				8026
		Mafdel	DEL/DRIVE	DD25
08594	AMIGO-1000-TMPLT-08594	Habasit	Cleandrive™	CD.M50.S-UA.CB
				CD.M50.S-UA.WB
				CD.M25.S-UA.CB CD.M25.S-UA.WB
08595	AMIG0-1000-TMPLT-08595			Flat
00090	AIVITOU-TUUU-TIVIFLT-00000			PC10
08596	AMIGO-1000-TMPLT-08596	Gates [®] Mectrol [®]	PosiClean [®]	PC20
08590	AIVIIGU-1000-11VIPLI-08090	UBR	1" Purclean	PS2
		Gates® Mectrol®	CenterClean®	CC40
00507		Daisler®	REOclean®	AT40
08597	AMIG0-1000-TMPLT-08597			
		UBR	Center Drive PurClean	CD3BLSS
08603	AMIGO-1000-TMPLT-08603	Ammeraal	Aeon	Aeon-50
				UBM
08710	AMIG0-1000-TMPLT-08710	Cog-veyor Systems Inc.	Cog-veyor	UWM
				PBH PWH
08739	AMIG0-1000-TMPLT-08739	Beltservice Corporation	Magnethane™	PD1
		Denservice corporation	Iviagiletilalle	
08741	AMIGO-1000-TMPLT-08741 AMIGO-1000-TMPLT-08776	Gates® Mectrol®	PosiLace™	Flat w/Spikes PC20
				CC40
08776				FC12
		UBR	Hinge Lace	N/A
	AMIGO-1000-TMPLT-08788	Daisler®	REOclean®	AT25
				REO-T50 DB & SB & V
		UBR	2" Purclean	PB3
		Volta	DualDrive™	FMW & FMB
08788 A				FHW & FHB
			Mini DualDrive™	FMB
				FHB
			Mini SuperDrive™	FMB
				FHB
08847	AMIG0-1000-TMPLT-08847	Volta	Hinge Splice	M (2.5-5mmH)
08849	AMIG0-1000-TMPLT-08849	Ammeraal Beltech	Soliflex PRO/	Soliflex TPU
			Soliflex PRO mini	Soliflex TPE
08855	AMIG0-1000-TMPLT-08855	Mafdel	POSITIVEBELT	P02-L
08856	AMIG0-1000-TMPLT-08856	Mafdel	DEL/DRIVE	DD50

Amigo[™] Optional Accessories

inge optional/lococortes				
	Ordering Number	Item Code		
Skiving Tool	RTBS Rough Top Skiver	03239		
Replacement Blades for Amigo	AMIGO-1000-BLADES-5	08587		
High – Low Temp Friction Tape for Flat Belts	AMIGO-FRICTIONTAPE-33X25	08604		

Authorised Distributor:

Flexco (Aust.) Pty. Ltd • 10 Solent Circuit, Norwest • NSW, Australia, 2153 • Australia Tel: 612-8818-2000 • Fax: 612-8824-6333 • E-mail: salesau@flexco.com

Visit www.flexco.com for other Flexco locations and products.

©2020 Flexible Steel Lacing Company. 03/05/20. For reorder: X5951

