

Quickly and Easily Remove Belt Top Cover to Recess Mechanical Fasteners

Whenever possible, Flexco recommends skiving the belt in order to countersink mechanical fasteners. Skiving reduces the fastener profile on the belt, resulting in improved fastener/cleaner compatibility and increased fastener service life.



Safe, On-Site Operation

Portable, lightweight, and easy to carry, the FSK™ Belt Skiver adjusts easily to the precise cutting depth you need. The blade is safely enclosed during skiving operations. The FSK is compact, so it is easy to use anywhere on the job site – even in cramped operating environments.

Used on rubber-covered belts with top covers of 3/16" (4.5 mm) or more, the FSK Skiver provides skives from 1/16" to 3/8" (1.5 to 9.5 mm) deep in a single pass. Deeper skives can be achieved with multiple passes. The FSK can also be used on most worn or damaged belt surfaces.

Save Time, Reduce Worker Fatigue with the Power Skiver



- Variable speed drill trigger provides you maximum control from start to finish.
- Power Skiver is up to 5X Faster than manual operation.
- The FSK2 and FSK2MP skives belts between 1/4" (6.5 mm) and 1-1/4" (32 mm) thick.
- The FSK2MXL skives belts between 7/8" (22.5 mm) and 1-3/4" (44.5 mm) thick.

Features and Benefits



Easily select and set the depth of the skive.



Front drive rollers aggressively grip belt at the start of the skive to prevent slippage.



Easily adjust fence for the appropriate fastener size.

FSK™ Belt Skiver

A Safer Way to Skive a Belt

The FSK™ Belt Skiver safely removes top cover for installation of recessed splices.

- Blade safely enclosed during skiving operations
- Portable and lightweight
- Ideal for rubber-covered belts with top covers 3/16" (4.5 mm) thick or more



FSK2M



The FSK2MP includes an attached cordless electric drill, two batteries, charger, and protective carrying case.



FSK2MP

Skive Capacity

Description	FSK2M/FSK2MP		FSK2MXL	
	in.	mm	in.	mm
Belt Thickness	1/4" – 1-1/4"	6.5 – 32 mm	7/8" – 1-3/4"	22.5 – 44.5 mm
Skive Depth	1/16" – 3/8"	1.5 – 9.5 mm	1/16" – 3/8"	1.5 – 9.5 mm
Skive Width	Up to 2-1/2"	Up to 64 mm	Up to 2-1/2"	Up to 64 mm

Ordering Information

Description	Ordering Number
Skiver Complete with Metal Fence*	FSK2M
Power Skiver Complete with Metal Fence*	FSK2MP
Skiver XL Complete with Metal Fence*	FSK2MXL

*Comes with standard blade

Authorized Distributor:



2525 Wisconsin Avenue • Downers Grove, IL 60515-4200 • USA
Tel: (630) 971-0150 • Fax: (630) 971-1180 • E-mail: info@flexco.com

Visit www.flexco.com for other Flexco locations and products.

©2021 Flexible Steel Lacing Company. 09-30-21. For Reorder: W1247

