

Product Handbook

EFFECTIVE JANUARY 1, 2023

IOTPH01

Flexco Elevate™



10 Solent Circuit, Norwest NSW 2153, Australia

Customer Service
+61 2 8818 2000

Fax
+61 2 8824 6333

www.flexco.com

What are the Benefits of Digital Solutions?*

- **Asset management:** Digital mapping of all installed cleaners at your location and across your operations provides visibility of assets and allows for more efficient resource planning.
- **Increased Productivity:** Elevate™ makes it easy to manage your belt cleaner service, you know exactly when and where to deploy maintenance support
- **Improved Safety:** Elevate™ reduces, and in most cases eliminates, the need for dangerous physical inspection along the beltlines.
- **No Guesswork:** Your team will know exactly when and where service is needed on Flexco cleaners from the convenience of the dashboard.
- **ROI from Day One:** Data insights are immediately transferred to your Elevate Dashboard so you can realise an increase in operational efficiency from day one.
- **Leverages Existing Assets:** The Elevate™ Platform works with your existing Flexco belt cleaners – no additional investment in cleaners is required.
- **Remarkably Easy:** From installation and activation, to app and dashboard, everything about Flexco Elevate™ is user-friendly and designed to make your job easier.

* Specific benefits vary between solutions

The Power of Insights

- **Data build insights:** Data are the foundation of insights, and more data collected on your site equates to more insights.
- **Ground truth:** Ground truth collection is the process of matching real-world situations to the data collected, and all insights are created based on ground truth validation.
- **Technology partners:** Flexco teams up with world-class partners to provide various development and data science features to turn data into insights as well as storing, securing and managing data for Flexco's digital solutions.

Evolving Tools

- **Unlike physically manufactured products, digital solutions are remotely upgraded over time to enable more features.** This continuous upgrade strategy allows users to have the most up-to-date security, insights and enhancements available (select feature enhancements will be fee-based).

Product Ordering Information

FLEXCO ELEVATE™ *i3 Device, i3 Dashboard, i3 App*

Flexco Elevate™ i3 Device

| COUNTRY | ORDERING NUMBER | ITEM CODE |
|-----------|-----------------|-----------|
| Australia | DVC-CLR1-AU | 91602 |

* Includes lifetime subscription.




Product Notes:

- i3 device is approved for all Flexco precleaner and secondary applications using Flexco blades or blade segments.
- Device accommodates 73mm pole; 60mm pole requires pole adapter.
- Subscription will not activate (start date) until the cleaner profile information is submitted.

Replacement Parts


| REF | DESCRIPTION | ORDERING NUMBER | ITEM CODE |
|-----|---|-----------------|-----------|
| 1 | i3 Device Back Cover Kit, Australia** (1 ea.) | DVCR-CLR-BC1AU | 91603 |
| 2 | i3 Device Back Cover Screw Pack (4 screws) | DVCR-CLR-BC2 | 91604 |
| 3 | i3 Device Battery (1 ea.) | DVCR-CLR-BTR1 | 91605 |
| 4 | i3 Device Top Cover** (1 ea. incl. screw & washer) | DVCR-CLR-TC2 | 91606 |
| 5 | i3 Device Top Cap Screw Pack (4 screws, 4 washers) | DVCR-CLR-TC3 | 91607 |
| 6 | i3 Device Top Cap Kit** (incl. top cap & 1 ea. items 4 & 5) | DVCR-CLR-TC1 | 91608 |
| 7 | i3 Device 60mm Pole Adapter (1 ea.) | DVCR-CLR-ADT | 91597 |
| 8a | i3 Device 73mm Pole Extender** (1 ea.) | DVCR-CLR-EX73 | 91595 |
| 8b | i3 Device 60mm Pole Extender** (1 ea.) | DVCR-CLR-EX60 | 91596 |

**Hardware included





Note:

- Back cover kits must be ordered according to the original installation country.



8a 8b




Specifications & Guidelines

FLEXCO ELEVATE™ i3 Device, i3 Dashboard, i3 App


Clearance Guidelines for Installation

| POLE LENGTH OUTSIDE THE TENSIONER | CLEARANCE RADIUS AROUND POLE* |
|-----------------------------------|-------------------------------|
| mm | mm |
| 90 | 200 |


*i3 device requires clearance to rotate (precleaner application) or compress (secondary cleaner application) as the blade/tip wears.



Pole length requirement
outside tensioner



Precleaner 200mm clearance
radius around pole



Secondary cleaner
travel clearance

Regulatory, Certifications, Standards, Explosive Environments

| AUSTRALIA |
|--------------------------|
| RCM, IP66, RoHS, IECEx** |

**Contact Flexco regarding specific standards

i3 Dashboard System Requirements

| BROWSER | DEVICE |
|-----------------------------------|--|
| Any (optimized for Google Chrome) | Desktop, tablet, or smartphone (optimization for all types is continuous process) |


i3 Mobile Application Requirements

| OPERATING SYSTEM | BLUETOOTH® WIRELESS COMMUNICATION | INTERNET CONNECTION (Cell Service) |
|------------------|-----------------------------------|------------------------------------|
| Android, iOS | Required | Not required |

Specifications:

- Temperature Rating: -30°C to +65°C (-20°C to +40°C in explosive environments)
- Battery type: Non-rechargeable, lithium metal thionyl chloride (Li/SOCl₂)
- i3 Dashboard and i3 Mobile App languages: English, Spanish, German, French
- i3 Dashboard and i3 Mobile App units: Imperial/Metric

U.S. Patent #: 10,836,585

 Flexco (Aust.) Pty. Ltd • 10 Solent Circuit, Norwest • NSW, Australia, 2153 • Australia
Tel: 612-8818-2000 • Fax: 612-8824-6333 • E-mail: salesau@flexco.com

Visit www.flexco.com for other Flexco locations and products.

©2022 Flexible Steel Lacing Company. 11/28/22. For reorder: W1471

