



Partners in Productivity

Product Name: Flex-Lag Adhesive  
Page: 1 of 7  
This version issued: February, 2024

## Section 1 - Identification of The Material and Supplier

Flexco (Aust) Pty Ltd  
10 Solent Circuit  
Baulkham Hills, NSW 2153

Phone: + 61 2 8818 2000 (office hours)  
Fax: + 61 (02) 8824 6333  
www.flexco.com.au

**Chemical nature:** Polychloroprene in a suitable solvent system.  
**Trade Name:** Flex-Lag Adhesive  
**Product Use:** Polychloroprene based adhesive.  
**Creation Date:** August, 2013  
**This version issued:** February, 2024 and is valid for 5 years from this date.

## Section 2 - Hazards Identification

### Statement of Hazardous Nature

**SUSMP Classification:** S5

**ADG Classification:** Class 3: Flammable liquids.

**UN Number:** 1133, ADHESIVES containing flammable liquid



### GHS Signal word: DANGER

Flammable liquids Category 2  
Skin Corrosion /Irritation Category 2  
Serious eye damage/eye irritation Category 2A  
Specific Target Organ Toxicity - Single Exposure Category 3  
Specific Target Organ Toxicity - Single Exposure Category 3  
Hazardous to aquatic environment Short term/Chronic Category 2

### HAZARD STATEMENT:

H225: Highly flammable liquid and vapour.  
AUH066: Repeated exposure may cause skin dryness or cracking.  
H315: Causes skin irritation.  
H319: Causes serious eye irritation.  
H335: May cause respiratory irritation.  
H336: May cause drowsiness or dizziness.  
H411: Toxic to aquatic life with long lasting effects.

### PREVENTION

P210: Keep away from heat, sparks, open flames and hot surfaces. - No smoking.  
P242: Use only non-sparking tools.  
P243: Take precautionary measures against static discharge.  
P261: Avoid breathing fumes, mists, vapours or spray.  
P264: Wash contacted areas thoroughly after handling.  
P271: Use only outdoors or in a well ventilated area.  
P280: Wear protective gloves, protective clothing and eye or face protection.

### RESPONSE

P312: Call a POISON CENTRE or doctor if you feel unwell.  
P301+P330+P331: IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.  
P303+P361+P353: IF ON SKIN (or hair): Remove immediately all contaminated clothing. Rinse skin with water.  
P304+P340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.  
P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P332+P313: If skin irritation occurs: Get medical advice.  
P337+P313: If eye irritation persists: Get medical advice.  
P391: Collect spillage.  
P370+P378: In case of fire, use carbon dioxide, dry chemical, foam, water fog. Alcohol resistant foam is the preferred firefighting medium but, if it is not available, normal foam can be used.

## SAFETY DATA SHEET

Issued by: Flexco (Aust) Pty Ltd

Phone: + 61 2 8818 2000 (office hours)

Poisons Information Centre: 13 1126 from anywhere in Australia, (0800 764 766 in New Zealand)



Partners in Productivity

Product Name: Flex-Lag Adhesive  
Page: 2 of 7  
This version issued: February, 2024

#### STORAGE

P402+P404: Store in a dry place. Store in a closed container.

P403+P235: Store in a well-ventilated place. Keep cool.

#### DISPOSAL

P501: If they can not be recycled, dispose of contents and containers to landfill (see Section 13 of this SDS).

### Emergency Overview

**Physical Description & Colour:** Black liquid.

**Odour:** Characteristic odour.

**Major Health Hazards:** irritating to eyes and respiratory system, repeated exposure may cause skin dryness or cracking, vapours may cause drowsiness and dizziness.

### Section 3 - Composition/Information on Ingredients

Ingredients	CAS No	Conc,%	TWA (mg/m <sup>3</sup> )	STEL (mg/m <sup>3</sup> )
Ethyl acetate	141-78-6	25-50	720	1440
2-methylpentane	107-83-5	10-25	not set	not set
Acetone	67-64-1	2.5-10	1185	2375
Distillates (petroleum), light distillate hydrotreating process, low-boiling	68410-97-9	2.5-10	not set	not set
Isoheptane	31394-54-4	2.5-10	not set	not set
Other non hazardous ingredients	secret	to 100	not set	not set

This is a commercial product whose exact ratio of components may vary slightly. Minor quantities of other non hazardous ingredients are also possible.

The SWA TWA exposure value is the average airborne concentration of a particular substance when calculated over a normal 8 hour working day for a 5 day working week. The STEL (Short Term Exposure Limit) is an exposure value that may be equalled (but should not be exceeded) for no longer than 15 minutes and should not be repeated more than 4 times per day. There should be at least 60 minutes between successive exposures at the STEL. The term "peak" is used when the TWA limit, because of the rapid action of the substance, should never be exceeded, even briefly.

### Section 4 - First Aid Measures

#### General Information:

You should call The Poisons Information Centre if you feel that you may have been poisoned, burned or irritated by this product. The number is 13 1126 from anywhere in Australia (0800 764 766 in New Zealand) and is available at all times. Have this SDS with you when you call.

**Inhalation:** If irritation occurs, contact a Poisons Information Centre, or call a doctor. Remove source of contamination or move victim to fresh air. If breathing is difficult, oxygen may be beneficial if administered by trained personnel, preferably on a doctor's advice. In severe cases, symptoms of pulmonary oedema can be delayed up to 48 hours after exposure.

**Skin Contact:** Wash gently and thoroughly with water (use non-abrasive soap if necessary) for 5 minutes or until chemical is removed.

**Eye Contact:** Immediately flush the contaminated eye(s) with lukewarm, gently flowing water for 20 minutes or until the product is removed, while holding the eyelid(s) open. Take care not to rinse contaminated water into the unaffected eye or onto the face. Obtain medical attention immediately. Take special care if exposed person is wearing contact lenses.

**Ingestion:** If swallowed, do NOT induce vomiting. Wash mouth with water and contact a Poisons Information Centre, or call a doctor.

### Section 5 - Fire Fighting Measures

**Fire and Explosion Hazards:** The major hazard in fires is usually inhalation of heated and toxic or oxygen deficient (or both), fire gases. There is a moderate risk of an explosion from this product if commercial quantities are involved in a fire. Firefighters should take care and appropriate precautions. Any explosion will likely spread the fire to surrounding materials. Water spray may be used to cool drums involved in a fire, reducing the chances of an explosion.

Fire decomposition products from this product may be toxic if inhaled. Take appropriate protective measures.

**Extinguishing Media:** In case of fire, use carbon dioxide, dry chemical, foam, water fog. Alcohol resistant foam is the preferred firefighting medium but, if it is not available, normal foam can be used. Try to contain spills, minimise spillage entering drains or water courses.

### SAFETY DATA SHEET

Issued by: Flexco (Aust) Pty Ltd

Phone: + 61 2 8818 2000 (office hours)

Poisons Information Centre: 13 1126 from anywhere in Australia, (0800 764 766 in New Zealand)



Partners in Productivity

Product Name: Flex-Lag Adhesive  
Page: 3 of 7  
This version issued: February, 2024

**Fire Fighting:** If a significant quantity of this product is involved in a fire, call the fire brigade. There is a danger of a violent reaction or explosion if significant quantities of this product are involved in a fire. Recommended personal protective equipment is full fire kit and breathing apparatus. Cool closed, undamaged containers exposed to fire with water spray.

**Flammability Class:** Flammable Category 2 (GHS); Highly Flammable (AS1940).

## Section 6 - Accidental Release Measures

**Accidental release:** In the event of a major spill, prevent spillage from entering drains or water courses. Evacuate the spill area and deny entry to unnecessary and unprotected personnel. Immediately call the Fire Brigade. Wear full protective clothing including eye/face protection. All skin areas should be covered. See below under Personal Protection regarding Australian Standards relating to personal protective equipment. Suitable materials for protective clothing include PE/EVAL, Responder, butyl rubber, Teflon. Eye/face protective equipment should comprise as a minimum, protective goggles. If there is a significant chance that vapours or mists are likely to build up in the cleanup area, we recommend that you use a respirator. It should be fitted with a type AX cartridge, suitable for low boiling point organic compounds. See manufacturer's specifications for detailed specifications.

Stop leak if safe to do so, and contain spill. Absorb onto sand, vermiculite or other suitable absorbent material. If spill is too large or if absorbent material is not available, try to create a dike to stop material spreading or going into drains or waterways. Avoid using sawdust or other combustible material. Any electrical equipment should be non-sparking. Any equipment capable of building an electrostatic charge should be electrically grounded. Sweep up and shovel or collect recoverable product into labelled containers for recycling or salvage, and dispose of promptly. Recycle containers wherever possible after careful cleaning. After spills, wash area preventing runoff from entering drains. If a significant quantity of material enters drains, advise emergency services. This material may be suitable for approved landfill. Ensure legality of disposal by consulting regulations prior to disposal. Thoroughly launder protective clothing before storage or re-use. Advise laundry of nature of contamination when sending contaminated clothing to laundry.

**Flash point:** <0°C  
**Upper Flammability Limit:** No data.  
**Lower Flammability Limit:** No data.  
**Autoignition temperature:** No data.

## Section 7 - Handling and Storage

**Handling:** Keep exposure to this product to a minimum, and minimise the quantities kept in work areas. Check Section 8 of this SDS for details of personal protective measures, and make sure that those measures are followed. The measures detailed below under "Storage" should be followed during handling in order to minimise risks to persons using the product in the workplace. Also, avoid contact or contamination of product with incompatible materials listed in Section 10.

**Storage:** This product is a Scheduled Poison. Observe all relevant regulations regarding sale, transport and storage of this schedule of poison. Store in a cool, well ventilated area, and make sure that surrounding electrical devices and switches are suitable. Check containers periodically for leaks. Containers should be kept closed in order to minimise contamination and possible evaporation. Make sure that the product does not come into contact with substances listed under "Incompatibilities" in Section 10. If you keep more than 2500kg or L of Dangerous Goods of Packaging Group II, you may be required to license the premises or notify your Dangerous Goods authority. If you have any doubts, we suggest you contact your Dangerous Goods authority in order to clarify your obligations. Check packaging - there may be further storage instructions on the label.

## Section 8 - Exposure Controls and Personal Protection

The following Australian Standards will provide general advice regarding safety clothing and equipment:

Respiratory equipment: **AS/NZS 1715**, Protective Gloves: **AS 2161**, Occupational Protective Clothing: AS/NZS 4501 set 2008, Industrial Eye Protection: **AS1336** and **AS/NZS 1337**, Occupational Protective Footwear: **AS/NZS2210**.

SWA Exposure Limits	TWA (mg/m <sup>3</sup> )	STEL (mg/m <sup>3</sup> )
Ethyl acetate	720	1440
Acetone	1185	2375

No special equipment is usually needed when occasionally handling small quantities. The following instructions are for bulk handling or where regular exposure in an occupational setting occurs without proper containment systems.

**Ventilation:** This product should only be used in a well ventilated area. If natural ventilation is inadequate, use of a fan is suggested.

## SAFETY DATA SHEET

Issued by: Flexco (Aust) Pty Ltd

Phone: + 61 2 8818 2000 (office hours)

Poisons Information Centre: 13 1126 from anywhere in Australia, (0800 764 766 in New Zealand)



Partners in Productivity

Product Name: Flex-Lag Adhesive

Page: 4 of 7

This version issued: February, 2024

**Eye Protection:** Protective glasses or goggles should be worn when this product is being used. Failure to protect your eyes may cause them harm. Emergency eye wash facilities are also recommended in an area close to where this product is being used.

**Skin Protection:** You should avoid contact even with mild skin irritants. Therefore you should wear suitable impervious elbow-length gloves and facial protection when handling this product. See below for suitable material types.

**Protective Material Types:** We suggest that protective clothing be made from the following materials: PE/EVAL, Responder, butyl rubber, Teflon.

**Respirator:** Usually, no respirator is necessary when using this product. However, if you have any doubts consult the Australian Standard mentioned above.

Safety deluge showers should, if practical, be provided near to where this product is being handled commercially.

## Section 9 - Physical and Chemical Properties:

<b>Physical Description &amp; colour:</b>	Black liquid.
<b>Odour:</b>	Characteristic odour.
<b>Boiling Point:</b>	Boils in a range above 56°C.
<b>Freezing/Melting Point:</b>	No specific data. Liquid at normal temperatures.
<b>Volatiles:</b>	74% w/w
<b>Vapour Pressure:</b>	Approx 10 kPa at 20°C
<b>Vapour Density:</b>	No data.
<b>Specific Gravity:</b>	0.86
<b>Water Solubility:</b>	Slightly soluble.
<b>pH:</b>	No data.
<b>Volatility:</b>	No data.
<b>Odour Threshold:</b>	No data.
<b>Evaporation Rate:</b>	No data.
<b>Coeff Oil/water Distribution:</b>	No data
<b>Particle Characteristics:</b>	Not applicable to liquids.
<b>Autoignition temp:</b>	No data.

## Section 10 - Stability and Reactivity

**Reactivity:** This product is unlikely to react or decompose under normal storage conditions. However, if you have any doubts, contact the supplier for advice on shelf life properties.

**Conditions to Avoid:** This product should be kept in a cool place, preferably below 30°C. Keep containers tightly closed. Containers should be kept dry. Keep containers and surrounding areas well ventilated. Keep away from sources of sparks or ignition. Handle and open containers carefully. Any electrical equipment in the area of this product should be flame proofed.

**Incompatibilities:** strong oxidising agents.

**Fire Decomposition:** Combustion forms carbon dioxide, and if incomplete, carbon monoxide and possibly smoke. Water is also formed. May form hydrogen chloride gas, other compounds of chlorine. Carbon monoxide poisoning produces headache, weakness, nausea, dizziness, confusion, dimness of vision, disturbance of judgment, and unconsciousness followed by coma and death.

**Polymerisation:** This product will not undergo polymerisation reactions.

## Section 11 - Toxicological Information

**Local Effects:**

**Target Organs:** There is no data to hand indicating any particular target organs.

## Classification of Hazardous Ingredients

Ingredient	Health Hazard Statement Codes
Ethyl Acetate	H225, H336, H319, AUH066
<ul style="list-style-type: none"><li>Flammable liquid - category 2</li><li>Specific target organ toxicity (single exposure) - category 3</li><li>Eye irritation - category 2A</li></ul>	

## SAFETY DATA SHEET

Issued by: Flexco (Aust) Pty Ltd

Phone: + 61 2 8818 2000 (office hours)

Poisons Information Centre: 13 1126 from anywhere in Australia, (0800 764 766 in New Zealand)



Partners in Productivity

Product Name: Flex-Lag Adhesive  
Page: 5 of 7  
This version issued: February, 2024

Acetone H225, H319, H336, AUH066

- Flammable liquid - category 2
- Eye irritation - category 2A
- Specific target organ toxicity (single exposure) - category 3

2-methylpentane H225, H304, H315, H336, H411

- Flammable liquid – category 2
- Aspiration hazard – category 1
- Skin irritation – category 2
- Specific target organ toxicity (single exposure) – category 3
- Hazardous to the aquatic environment (chronic) – category 2

Distillates (petroleum), light distillate hydrotreating process, low-boiling H304, H350, H340, H319, H315, H372

- Aspiration hazard – category 1
- Carcinogenicity – category 1A
- Germ cell mutagenicity – category 1B
- Eye irritation – category 2A
- Skin irritation – category 2
- Specific target organ toxicity (repeated exposure) – category 1

Isoheptane H225, H304, H315, H336, H410

- Flammable liquid – category 2
- Aspiration hazard – category 1
- Skin irritation – category 2
- Specific target organ toxicity (single exposure) – category 3
- Hazardous to the aquatic environment (chronic) – category 1
- Hazardous to the aquatic environment (acute) – category 1

#### Light, Hydrotreated Petroleum Naphtha:

LD<sub>50</sub> Oral, Rat >2000mg/kg

LD<sub>50</sub> Dermal, Rat = >2000mg/kg

LC<sub>50</sub> Inhalation, Rat = 190mg/L/4hr

### Potential Health Effects

#### Inhalation:

**Short Term Exposure:** High vapour pressures may cause drowsiness and dizziness. In addition product is an inhalation irritant. Symptoms may include headache, irritation of nose and throat and increased secretion of mucous in the nose and throat. Other symptoms may also become evident, but they should disappear after exposure has ceased.

**Long Term Exposure:** Vapours may cause drowsiness and dizziness.

#### Skin Contact:

**Short Term Exposure:** Available data indicates that this product is not harmful. It should present no hazards in normal use. However product may be irritating, but is unlikely to cause anything more than mild transient discomfort.

**Long Term Exposure:** Repeated exposure may cause skin dryness or cracking.

#### Eye Contact:

**Short Term Exposure:** This product is an eye irritant. Symptoms may include stinging and reddening of eyes and watering which may become copious. Other symptoms may also become evident. If exposure is brief, symptoms should disappear once exposure has ceased. However, lengthy exposure or delayed treatment may cause permanent damage.

**Long Term Exposure:** No data for health effects associated with long term eye exposure.

#### Ingestion:

**Short Term Exposure:** Significant oral exposure is considered to be unlikely. However, this product is an oral irritant. Symptoms may include burning sensation and reddening of skin in mouth and throat. Other symptoms may also become evident, but all should disappear once exposure has ceased.

**Long Term Exposure:** No data for health effects associated with long term ingestion.

#### Carcinogen Status:

**SWA:** No significant ingredient is classified as carcinogenic by SWA.

### SAFETY DATA SHEET

Issued by: Flexco (Aust) Pty Ltd

Phone: + 61 2 8818 2000 (office hours)

Poisons Information Centre: 13 1126 from anywhere in Australia, (0800 764 766 in New Zealand)



Partners in Productivity

Product Name: Flex-Lag Adhesive

Page: 6 of 7

This version issued: February, 2024

**NTP:** No significant ingredient is classified as carcinogenic by NTP.

**IARC:** No significant ingredient is classified as carcinogenic by IARC.

## Section 12 - Ecological Information

Toxic to aquatic organisms, may cause long-term adverse effects to the aquatic environment. Insufficient data to be sure of status.

## Section 13 - Disposal Considerations

**Disposal:** This product may be recycled if unused, or if it has not been contaminated so as to make it unsuitable for its intended use. If it has been contaminated, it may be possible to reclaim the product by filtration, distillation or some other means. If neither of these options is suitable, consider controlled incineration, or landfill.

## Section 14 - Transport Information

**Dangerous according to Australian Dangerous Goods (ADG) Code, IATA and IMDG/IMSBC criteria.**

**UN Number:** 1133, ADHESIVES containing flammable liquid

**Hazchem Code:** •3YE

**Special Provisions:** None allocated

**Limited quantities:** ADG 7 specifies a Limited Quantity value of 5 L for this class of product.

**Dangerous Goods Class:** Class 3: Flammable liquids.

**Packaging Group:** II

**Packaging Method:** P001, IBC02

Class 3 Flammable Liquids shall not be loaded in the same vehicle or packed in the same freight container with Classes 1 (Explosives), 2.1 (Flammable Gases where flammable liquids and flammable gases are both in bulk), 2.3 (Toxic Gases), 4.2 (Spontaneously Combustible Substances), 5.1 (Oxidising Agents), 5.2 (Organic Peroxides), 6 (Toxic Substances, except Flammable Liquid is nitromethane), and 7 (Radioactive Substances). They may however be loaded in the same vehicle or packed in the same freight container with Classes 2.1 (Flammable Gases except where the Flammable Liquids and Flammable Gases are in bulk), 2.2 (Non-Flammable Non-Toxic Gases), 4.1 (Flammable Solids), 4.3 (Dangerous When Wet Substances), 6 (Toxic Substances, where Flammable Liquid is nitromethane), 8 (Corrosive Substances), 9 (Miscellaneous Dangerous Goods), Foodstuffs or foodstuff empties.

## Section 15 - Regulatory Information

**AIC:** All of the significant ingredients in this formulation are compliant with AICIS regulations.

The following ingredients: Light, hydrotreated petroleum naphtha (a liquid hydrocarbon), Acetone, are mentioned in the SUSMP.

## Section 16 - Other Information

**This SDS contains only safety-related information. For other data see product literature.**

### Acronyms:

<b>ADG Code</b>	Australian Code for the Transport of Dangerous Goods by Road and Rail (7 <sup>th</sup> edition)
<b>AIC</b>	Australian Inventory of Industrial Chemicals
<b>SWA</b>	Safe Work Australia, formerly ASCC and NOHSC
<b>CAS number</b>	Chemical Abstracts Service Registry Number
<b>Hazchem Code</b>	Emergency action code of numbers and letters that provide information to emergency services especially firefighters
<b>IARC</b>	International Agency for Research on Cancer
<b>NOS</b>	Not otherwise specified
<b>NTP</b>	National Toxicology Program (USA)
<b>SUSMP</b>	Standard for the Uniform Scheduling of Medicines & Poisons
<b>UN Number</b>	United Nations Number

THIS SDS SUMMARISES OUR BEST KNOWLEDGE OF THE HEALTH AND SAFETY HAZARD STATEMENT: INFORMATION OF THE PRODUCT AND HOW TO SAFELY HANDLE AND USE THE PRODUCT IN THE WORKPLACE. EACH USER MUST REVIEW THIS SDS IN THE CONTEXT OF HOW THE PRODUCT WILL BE HANDLED AND USED IN THE WORKPLACE.

IF CLARIFICATION OR FURTHER INFORMATION IS NEEDED TO ENSURE THAT AN APPROPRIATE RISK ASSESSMENT CAN BE MADE, THE USER SHOULD CONTACT THIS COMPANY SO WE CAN ATTEMPT TO OBTAIN ADDITIONAL INFORMATION FROM OUR SUPPLIERS. OUR RESPONSIBILITY FOR PRODUCTS SOLD IS SUBJECT TO OUR STANDARD TERMS AND CONDITIONS, A COPY OF WHICH IS SENT TO OUR CUSTOMERS AND IS ALSO AVAILABLE ON REQUEST.

## SAFETY DATA SHEET

Issued by: Flexco (Aust) Pty Ltd

Phone: + 61 2 8818 2000 (office hours)

Poisons Information Centre: 13 1126 from anywhere in Australia, (0800 764 766 in New Zealand)



*Partners in Productivity*

Product Name: Flex-Lag Adhesive  
Page: 7 of 7  
This version issued: February, 2024

Please read all labels carefully before using product.

This SDS is prepared in accord with the SWA document "Preparation of Safety Data Sheets for Hazardous Chemicals - Code of Practice" (July 2020) and GHS Revision 7

Copyright © Kilford & Kilford Pty Ltd, February, 2024.

<http://www.kilford.com.au/> Phone (02)8321 8866

W1934 04/10/24

#### **SAFETY DATA SHEET**

Issued by: Flexco (Aust) Pty Ltd

Phone: + 61 2 8818 2000 (office hours)

**Poisons Information Centre: 13 1126 from anywhere in Australia, (0800 764 766 in New Zealand)**