

SMARTCLAMP™

Belt Clamps

A Complete System to Work Safer and Smarter

As part of Flexco Safe™ belt conveyor maintenance solutions, the SmartClamp™ system provides both safety and efficiency when clamping belts for installation of Anker® and Alligator® mechanical belt fasteners.



Patents: www.flexco.com/patents

Safer.

The SmartClamp was engineered to maximize strength and performance. The wedge grip design places an evenly distributed pressure load over the entire clamp interface. The set of four clamps permits safe pulling of belts with up to 900 kg (2,000 lbs.) of take-up load. Each individual clamp is rated up to a 450 kg (1,000 lb.) load.

Faster.

Unlike other clamp systems which require time-consuming adjustments, the SmartClamp™ needs only a quick tap of a hammer to prelock the wedges. Attach and tighten come-alongs and the final lock is engaged. This fast setup saves precious and costly time during a breakdown situation.


With SmartClamps you do not need to sacrifice efficiencies for safety. These easy-to-install belt clamps make the choice obvious for maximum belt conveyor uptime.

Smarter.


Features and Benefits



Large impact plate provides easy striking surface.



Return Spring Post holds wedges up so belt can easily slide into clamping position.



Ribbed lower wedge and grooved housing provide additional holding strength (a).

Beveled edges of the housing permit easy belt engagement. Elimination of sharp corners and edges provide a smoother transition from clamp to belt, reducing the chance of belt damage (b).

SMARTCLAMP™ Belt Clamps



Ordering Information

Ordering Number	Item Code	Weight		Belt Thickness	
		kgs.	lbs.	mm	in.
SMARTCLAMP	04073	21.0	45.0	up to 8	up to 5/16

Note: A complete set of SmartClamps includes four clamps with two convenient carrying bags.

Other Flexco Safe™ Products:

900 Series Belt Cutter

Designed to enhance operator safety with the fully enclosed cutting blade, this lightweight, portable belt cutter delivers straight, accurate cuts, time after time. Available in five widths: 600, 900, 1200, 1500, and 1800 mm (24", 36", 48", 60" and 72").



Authorised Distributor:

Unit 7 Kingsmark Freeway • Oakenshaw • Bradford, BD12 7HW • United Kingdom
Tel: +44-1274-600-942 • Fax: +44-1274-673-644 • Email: sales@flexco.co.uk

Visit www.flexco.com for other Flexco locations and products.

©2018 Flexible Steel Lacing Company. Clipper® and Alligator® are registered trademarks. 12-10-21. For reorder: X1837

