




UNIBAR® Rectangular High Tensile Fasteners

All the advantages of Unibar® fasteners combined with a new high-strength, abrasion-resistant, shaped 430 Stainless Steel wire provide for increased belt conveyor uptime.



Cross-section
of wire



Easier.

Individual hooks are welded to a common bar forming a continuous strip of fasteners. This technology simplifies installation by making them easier to handle, install, mesh ends together, and insert the connecting pin. Available in 12" and 24" (300 and 600 mm) widths standard and custom lengths up to 60" (1500 mm).

Stronger.

The unique shaped 430 Stainless Steel wire (.052" wide x .057" high) provides 22% additional wire mass, yielding significantly higher abrasion resistance than hooks made out of standard .054" round wire. In addition, the U3RHTS Unibar fasteners provide 36% greater pull-out strength than standard U3 offerings.

Faster.

Installing Unibar fasteners is quicker than installing carded hooks. This is due to the easily removed Safety Strip which covers the hook points during handling, the common bar advantages keeping the hooks parallel and flat when installed, and the wider widths available.

Smarter.

Ordering Information						
Fastener Size	Belt Thickness Range		Minimum Pulley Diameter		Item Code	Ordering Number
	in.	mm	in.	mm		
12" (12/Box)						
U3-1RHTS	1/8-5/32	3.2-4.0	3 ½	89	05338	U3-1RHTS12
U3-2RHTS	5/32-3/16	4.0-4.8	3 ½	89	05339	U3-2RHTS12
U3RHTS	3/16-7/32	4.8-5.6	3 ½	89	05340	U3RHTS12
24" (10/Box)						
U3-1RHTS	1/8-5/32	3.2-4.0	3 ½	89	05341	U3-1RHTS24
U3-2RHTS	5/32-3/16	4.0-4.8	3 ½	89	05342	U3-2RHTS24
U3RHTS	3/16-7/32	4.8-5.6	3 ½	89	05343	U3RHTS24

Authorized Distributor:



2525 Wisconsin Avenue • Downers Grove, IL 60515-4200 • USA
Tel: (630) 971-0150 • Fax: (630) 971-1180 • E-mail: info@flexco.com

Visit www.flexco.com for other Flexco locations and products.

©2008 Flexible Steel Lacing Company. Clipper® and Unibar® are registered trademarks. 12-13. For Reorder: X2068

