


# CHEVRON Belt Cleaner

## A Better Cleaning Solution

Chevron, cleated and raised rib belts present a special problem for efficient cleaning. However, not cleaning these belts lets the carryback move along the return belt and cause all the familiar problems: mistracking, buildup and premature wear on idler rollers and resulting belt wear and damage. Flexco's Chevron Belt Cleaner takes a new approach to cleaning these problem belts.



*50mm (2") rubber fingers gently dislodge carryback from chevron or raised ribs*

*Option to remove and replace 75mm (3")-wide rubber finger ring segments individually or as a complete drum*



*Versatile tensioner kit can be mounted to push-up or pull-up the cleaner*

*Quick drum replacement. Simply loosen the set screws, slide off the old drum, slide on the new one and retighten the screws*

## Features and Benefits

- **Free-rotating.** Works only when the belt runs.
- **Self-cleaning.** Finger length, spacing, and the rotary action allows the carryback to fall free instead of clogging.
- **Long-wearing SBR rubber.** Drum life ranges from 1 to 3 years depending upon the application conditions and the material being conveyed.
- **Easy to install.** Few parts and easy-to-use installation instructions make the job simple.
- **Works on mechanically spliced or vulcanized belts.**
- **Works on reversing belts.**

# CHEVRON Belt Cleaner

## Specifications and Guidelines

- **Maximum Belt Speed**  
2.5 m/s (500 FPM)
- **Temperature Rating**  
-35° C to 82° C (-30°F to 180° F)
- **Overall Diameter**  
238mm (9-1/2")
- **Cleaner Material**  
Rubber 45-A durometer
- **CEMA Cleaner Rating**  
Class 3
- **Shaft Length**  
Belt Width + 750mm (30")
- **Shaft Size**  
25mm (1") Hex Shaft
- **Finger Length**  
50mm (2")
- **Rubber Finger Ring Width**  
75mm (3")
- **Maximum Chevron or Cleat Height**  
25mm (1")
- **Available for Belt Widths**  
450 to 2100mm (18" to 84")
- **Horizontal Clearance Required**  
250mm (10")
- **Vertical Clearance Required**  
250mm (10")


## Ordering Information

Chevron Belt Cleaner					
Belt Width		Blade Coverage		Ordering Number	Item Code
mm	in.	mm	in.		
450	18	450	18	CBC18	76668
600	24	600	24	CBC24	76669
750	30	750	30	CBC30	76670
900	36	900	36	CBC36	76671
1050	42	1050	42	CBC42	76672
1200	48	1200	48	CBC48	76673
1350	54	1350	54	CBC54	76674
1500	60	1500	60	CBC60	76675
1800	72	1800	72	CBC72	90762
2100	84	2100	84	CBC84	90763

Replacement Drums		
Description	Ordering Number	Item Code
450mm (18") Repl Drum with Fingers	CRDF18	90631
600mm (24") Repl Drum with Fingers	CRDF24	90632
750mm (30") Repl Drum with Fingers	CRDF30	90633
900mm (36") Repl Drum with Fingers	CRDF36	90634
1050mm (42") Repl Drum with Fingers	CRDF42	90635
1200mm (48") Repl Drum with Fingers	CRDF48	90636
1350mm (54") Repl Drum with Fingers	CRDF54	90637
1500mm (60") Repl Drum with Fingers	CRDF60	90638
1800mm (72") Repl Drum with Fingers	CRDF72	90639
2100mm (84") Repl Drum with Fingers	CRDF84	90640

Replacement Finger Rings		
Description	Ordering Number	Item Code
Individual 75mm (3") Repl Finger Ring	CBC3R	90641

## Flexco Chevron Belt Cleaner



- + Self-cleaning fingers.
- + Rubber fingers are gentle on belt's top cover.
- + Passive - moves only when the belt is running.
- + Finger wear life is 1 to 3 years.
- + Drum change is quick and easy.

Authorized Distributor:

240 Macpherson Road • #02-01 • Singapore 348574  
Tel: +65-6484-1533 • Fax: +65-6484-1531 • E-mail: [asiasales@flexco.com](mailto:asiasales@flexco.com)

Visit [www.flexco.com](http://www.flexco.com) for other Flexco locations and products.

©2019 Flexible Steel Lacing Company. 07/25/19. For reorder: X2798

