


FLEXCO® SR™ RIVET HINGED Installation

Lightweight Aluminum MSRT Installation Tool

The easy to use Aluminum MSRT tool now complements our Flexco® SR™ Fastening System with a focus on providing a lightweight, portable application tool. The Aluminum MSRT is designed to assist splice installers in harsh working environments where heavy splicing equipment has to be moved on a regular basis.



Fast, accurate positioning of fastener strips.



Riser plate allows for smooth transition of belt into fastener strips.

Easier.

The new scalloped design of the riser plate allows for fast, accurate alignment of fastener strips on the anvil plate.

The riser plate positions the belt for easier feed into the fastener strips.

Stronger.

Robust design of clamp bar with Acme threading provides maximum holding capabilities, especially on thick, high tension belts where a safe, strong hold is required.

Clamp bar and riser plate have been designed with serrated grips for more secure clamping and operator efficiency.

Faster.

Use Rapid Loader™ Collated Rivet Strips to load 20 rivets at one time for reduced installation time and increased operator efficiency.

Smarter.

Features and Benefits



Specially machined Scalloped Edge™ on riser plate allows fasteners to nest securely for accurate alignment of fasteners.



Heavier duty clamping methods with Acme threading to speed clamping time and ensure maximum holding ability even on thick, high tension belting.



Easy installation of rivets with Rapid Loader™ Collated Rivet strips. Load the entire guide block with one strip of collated rivets.

FLEXCO® SR™ RIVET HINGED Installation

Aluminum MSRT, MSRT8 & MSRT9 Multiple Rivet Driving Tools

Designed for ease-of-use and portability to make multiple rivet driving simple and fast. The Aluminum MSRT tools hold the belt, fastener strip, and guide blocks securely in place allowing for a low profile, even tension finished splice. The Aluminum MSRT Applicator includes two SR700 Multiple Guide Blocks, two SR759 Multiple Drive Rods, two 4 lb. Hammers, Lubricant, and one Canvas Carry Bag.



Patent Pending

Ordering Information

Aluminum MSRT Applicator Complete			
Belt Width		Ordering Number	Item Code
mm	in.		
750	30	MSRT-30-AL	40771
900	36	MSRT-36-AL	40773
1050	42	MSRT-42-AL	40775
1200	48	MSRT-48-AL	40776
1500	60	MSRT-60-AL	40782
1800	72	MSRT-72-AL	40783
2130	84	MSRT-84-AL	40784
2430	96	MSRT-96-AL	40785
Aluminum MSRT8 Applicator Complete			
1200	48	MSRT8-48-AL	41115
1500	60	MSRT8-60-AL	41116
1800	72	MSRT8-72-AL	41117
2130	84	MSRT8-84-AL	41118
2430	96	MSRT8-96-AL	41119
Aluminum MSRT9 Applicator Complete			
1200	48	MSRT9-48-AL	41812
1500	60	MSRT9-60-AL	41813
1800	72	MSRT9-72-AL	41814
2130	84	MSRT9-84-AL	41815

Aluminum Content

Aluminum Alloy Type	Percent	
	Mg Magnesium	Ti Titanium
5356	5.5	0.2
6005	0.6	0.1
6061	1.0	0.0
7075	2.5	0.0

Authorised Distributor:

New Door No. 51 • Anna Salai, Nagalkeni • Pammal Village • Chennai - 600 044 • Tamil Nadu • India
Tel: +91-44-4856-6762 • E-mail: info.india@flexco.com

Visit www.flexco.com for other Flexco locations and products.

©2014 Flexible Steel Lacing Company. Flexco® is a registered trademark. 02-18-19. For Reorder: X3564

