


P-TYPE® Secondary Belt Cleaner

Reliable Secondary Belt Cleaner

The Flexco P-Type® Secondary Belt Cleaner is compact and designed to be positioned just off the head pulley to remove carryback from the belt. Stand alone, or when used in conjunction with a precleaner, the P-Type cleaner is a reliable choice for maintaining a highly efficient cleaning system.



Features and Benefits

- **Cleaning efficiency of metal blades.** The thin, hard edges of the metal blades deliver high cleaning efficiency and long wear life.
- **Works with Flexco mechanical splices.** The C-Tip tungsten carbide blades are impact-resistant, and the spring cushion allows them to move away from a passing splice without damage and with minimal cleaning disruption. V-Tip can be used only on vulcanized belts.
- **A complete cleaning system.** When the P-Type is teamed with a primary cleaner the system provides maximum cleaning power for tough applications.
- **Fits most conveyor structures.** Available for belt widths from 450mm to 1800mm (18" to 72").

P-TYPE® Secondary Belt Cleaner

Specifications and Guidelines

Maximum Belt Speed

5 m/s (1000 FPM)

Temperature Rating

-35° C to 82° C (-30° F to 180° F)

Usable Blade Wear Length

9 mm (3/8")

Blade Material



Impact resistant, long-lasting tungsten carbide (C-Tip for mechanical fasteners, V-Tips for vulcanized belts)

Available for Belt Widths

450 to 1800mm (18" to 72")

CEMA Cleaner Rating

Class 4



Pole Length

Cleaner size up to 1200mm (48") + 750mm (30")/

Cleaner size 1350mm (54") and up + 850mm (34")

Maximum Conveyor Span

Cleaner size up to 1200mm (48") + 625mm (25")/

Cleaner size 1350mm (54") and up + 725mm (29")

Horizontal Clearance Required

100mm (4")

Vertical Clearance Required

200mm (8")

Ordering Information

P-Type® Secondary with C-Tips*

Belt Width	Ordering	Item
mm	Number	Code
450	PC18	74566
600	PC24	74567
800	PC30	74568
1000	PC36	74569
1200	PC42	74570
1400	PC48	74571
1500	PC54	74572
1600	PC60	74573
1800	PC72	74574

*NOTE: C-Tips can be used on mechanically spliced and vulcanized belts. P-Type cleaners come standard with Select Set™ Tensioners.

P-Type® Secondary with V-Tips*

Belt Width	Ordering	Item
mm	Number	Code
450	PV-18	78453
600	PV-24	78415
750	PV-30	78417
900	PV-36	78419
1050	PV-42	78421
1200	PV-48	78423
1350	PV-54	78454
1500	PV-60	78455
1800	PV-72	73438

*NOTE: V-Tips can be used ONLY on vulcanized belts. P-Type cleaners come standard with Select Set™ Tensioners.

Replacement Tips

Ordering	Item
Number	Code
ICT6	74535
PSA150	73156

Lead time: 1 working day

Tips Required per Cleaner Size

mm	450	600	750	900	1050	1200	1350	1500	1800
in.	18	24	30	36	42	48	54	60	72
C-Tips or V-Tips Required	3	4	5	6	7	8	9	10	12

Additional Information

For size restricted applications, see the P-Type LS (Limited Space) Sell Sheet X2479.



Authorized Distributor:

Flexco Europe GmbH • Maybachstrasse 9 • 72348 Rosenfeld • Deutschland
Tel: +49-7428-9406-0 • Fax: +49-7428-9406-260 • E-mail: europe@flexco.com

Visit www.flexco.com for other Flexco locations and products.

©2020 Flexible Steel Lacing Company. 06/01/20. For reorder: X6037

